

Print Date
May-31-2015

Revision Date
May-31-2015

Revision Number
1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code **ADE89**
Product name **Red Toner**
Product category **ADE Series Epoxy Screen Ink**

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: 1-913-422-1888	Stockport, England SK4 3EG
Tel: 1-800-677-4657	Tel: +44 161 442 2111
Fax: 1-913-422-2294	
www.nazdar.com	

Emergency telephone number

USA: Chemtrec: 1-800-424-9300
Outside USA: Chemtrec: 1-703-527-3887
24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Flammable liquids	Category 3 - (H226)

Label elements



Signal Word

Warning

Hazard Statements

H319 - Causes serious eye irritation
H226 - Flammable liquid and vapor

Precautionary Statements

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Hazards not otherwise classified (HNOC)

May be harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Mixture**

Component	CAS-No	Weight %	Trade Secret	Note
Dipropylene Glycol Monomethyl Ether	34590-94-8	10 - 30	*	
Diacetone alcohol	123-42-2	5 - 10	*	
Propylene glycol monomethyl ether	107-98-2	1 - 5	*	
2-Butoxyethanol	111-76-2	1 - 5	*	

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of first aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion

DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**Foam. Carbon dioxide (CO₂). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.**Unsuitable Extinguishing Media**

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Component	ACGIH TLV
Dipropylene Glycol Monomethyl Ether 34590-94-8	TWA: 100 ppm STEL: 150 ppm Skin
Diacetone alcohol 123-42-2	TWA: 50 ppm
Propylene glycol monomethyl ether 107-98-2	TWA: 100 ppm STEL: 150 ppm
2-Butoxyethanol 111-76-2	TWA: 20 ppm

Component	OSHA PEL
Dipropylene Glycol Monomethyl Ether 34590-94-8	TWA: 100 ppm TWA: 600 mg/m ³ STEL: 150 ppm STEL: 900 mg/m ³ Skin
Diacetone alcohol 123-42-2	TWA: 50 ppm TWA: 240 mg/m ³
Propylene glycol monomethyl ether 107-98-2	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³
2-Butoxyethanol 111-76-2	TWA: 25 ppm TWA: 120 mg/m ³ TWA: 50 ppm TWA: 240 mg/m ³ Skin

Component	Ontario TWAEV
Dipropylene Glycol Monomethyl Ether 34590-94-8	TWA: 100 ppm STEL: 150 ppm

	Skin
Diacetone alcohol 123-42-2	TWA: 50 ppm TWA: 240 mg/m ³ STEL: 75 ppm STEL: 360 mg/m ³
Propylene glycol monomethyl ether 107-98-2	TWA: 100 ppm STEL: 150 ppm
2-Butoxyethanol 111-76-2	TWA: 20 ppm

Component	Mexico OEL (TWA)
Dipropylene Glycol Monomethyl Ether 34590-94-8	TWA/LMPE-PPT: 100 ppm TWA/LMPE-PPT: 60 mg/m ³ STEL/LMPE-CT: 150 ppm STEL/LMPE-CT: 900 mg/m ³
Diacetone alcohol 123-42-2	TWA/LMPE-PPT: 50 ppm TWA/LMPE-PPT: 240 mg/m ³ STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 360 mg/m ³
2-Butoxyethanol 111-76-2	TWA/LMPE-PPT: 26 ppm TWA/LMPE-PPT: 120 mg/m ³ STEL/LMPE-CT: 75 ppm STEL/LMPE-CT: 360 mg/m ³

Appropriate engineering controls

Engineering Measures Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face Protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Appearance	Colored Liquid
Odor	Characteristic	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		No data available
Melting point/freezing point		No data available
Boiling point/Boiling Range	> 149 °C / 300 °F	
Flash Point	52 °C / 125 °F	Setaflash closed cup
Evaporation rate		No data available
Flammability Limit in Air		
Upper flammability limit		No data available
Lower flammability limit		No data available
Vapor Pressure		No data available

Vapor Density No data available
 Specific Gravity 1.1
 Water Solubility No data available
 Solubility in other solvents No data available
 Partition coefficient: n-octanol/water No data available
 Autoignition Temperature No data available
 Decomposition temperature No data available
 Kinematic viscosity No data available
 Dynamic viscosity No data available

Explosive Properties No data available
 Oxidizing Properties No data available

Other Information

Photochemically Reactive No
 Weight Per Gallon (lbs/gal) 9.21

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
37.44	39.2	3.45	413.61

10. STABILITY AND REACTIVITY

Reactivity
 No information available.

Chemical stability
 Stable under normal conditions.

Possibility of Hazardous Reactions
 None under normal processing.

Conditions to avoid
 Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials
 Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products
 Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation There is no data for this product.
Eye Contact There is no data for this product.
Skin Contact There is no data for this product.
Ingestion There is no data for this product.

Component	Oral LD50
Dipropylene Glycol Monomethyl Ether 34590-94-8	5230 mg/kg (Rat)
Diacetone alcohol 123-42-2	4 g/kg (Rat)
Propylene glycol monomethyl ether 107-98-2	5200 mg/kg (Rat)
2-Butoxyethanol 111-76-2	470 mg/kg (Rat)

Component	LD50 Dermal
Dipropylene Glycol Monomethyl Ether	9500 mg/kg (Rabbit)

34590-94-8	
Diacetone alcohol 123-42-2	13500 mg/kg (Rabbit)
Propylene glycol monomethyl ether 107-98-2	13000 mg/kg (Rabbit)
2-Butoxyethanol 111-76-2	2270 mg/kg (Rat) 220 mg/kg (Rabbit)

Component	Inhalation LC50
Propylene glycol monomethyl ether 107-98-2	54.6 mg/L (Rat) 4 h >24 mg/L (Rat) 1 h
2-Butoxyethanol 111-76-2	2.21 mg/L (Rat) 4 h 450 ppm (Rat) 4 h

Information on toxicological effects

Symptoms There is no data for this product.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation There is no data for this product.
Eye damage/irritation There is no data for this product.
Irritation There is no data for this product.
Corrosivity There is no data for this product.
Sensitisation There is no data for this product.
Mutagenic Effects There is no data for this product.
Reproductive Effects There is no data for this product.
STOT - single exposure There is no data for this product.
STOT - repeated exposure There is no data for this product.
Chronic Toxicity There is no data for this product.
Aspiration hazard There is no data for this product.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH
2-Butoxyethanol 111-76-2	A3

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 7,930.00 mg/kg
ATEmix (dermal) 18,145.00 mg/kg mg/l
ATEmix (inhalation-dust/mist) 80.30 mg/l
ATEmix (inhalation-vapor) 431.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

0% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Component	Fish
Dipropylene Glycol Monomethyl Ether 34590-94-8	96h LC50 Pimephales promelas: >10000 mg/L [static]
Diacetone alcohol 123-42-2	96h LC50 Lepomis macrochirus: 420 mg/L 96h LC50 Lepomis macrochirus: 420 mg/L [static]
Propylene glycol monomethyl ether 107-98-2	96h LC50 Leuciscus idus: 4600 - 10000 mg/L [static] 96h LC50 Pimephales promelas: 20.8 g/L [static]

2-Butoxyethanol 111-76-2	96h LC50 Lepomis macrochirus: 1490 mg/L [static] 96h LC50 Lepomis macrochirus: 2950 mg/L
Component	Crustacea
Dipropylene Glycol Monomethyl Ether 34590-94-8	48h LC50 Daphnia magna: 1919 mg/L
Diacetone alcohol 123-42-2	24h EC50 Daphnia magna: 8750 mg/L
Propylene glycol monomethyl ether 107-98-2	48h EC50 Daphnia magna: 23300 mg/L
2-Butoxyethanol 111-76-2	24h EC50 Daphnia magna: 1698 - 1940 mg/L 48h EC50 Daphnia magna: >1000 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Component	Partition coefficient
Dipropylene Glycol Monomethyl Ether 34590-94-8	-0.064
Diacetone alcohol 123-42-2	1.03
Propylene glycol monomethyl ether 107-98-2	-0.437
2-Butoxyethanol 111-76-2	0.81

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods

Contain and dispose of waste according to local regulations.

Contaminated Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

DOT

In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

UN/ID no. UN1210
Proper Shipping Name Printing Ink
Hazard Class 3
Packing Group III

ICAO / IATA / IMDG / IMO

UN/ID no. UN1210
Proper Shipping Name Printing Ink
Hazard Class 3
Packing Group III

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier

(manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
2-Butoxyethanol	111-76-2	1 - 5	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

U.S. State Regulations

Component	Massachusetts Right To Know
Dipropylene Glycol Monomethyl Ether 34590-94-8	X
Diacetone alcohol 123-42-2	X
Propylene glycol monomethyl ether 107-98-2	X
2-Butoxyethanol 111-76-2	X

Component	Minnesota Right To Know
Dipropylene Glycol Monomethyl Ether 34590-94-8	X
Diacetone alcohol 123-42-2	X
Propylene glycol monomethyl ether 107-98-2	X
2-Butoxyethanol 111-76-2	X

Component	New Jersey Right To Know
Dipropylene Glycol Monomethyl Ether 34590-94-8	X
Diacetone alcohol 123-42-2	X
Propylene glycol monomethyl ether 107-98-2	X
2-Butoxyethanol 111-76-2	X

Component	Pennsylvania Right To Know
Dipropylene Glycol Monomethyl Ether 34590-94-8	X
Diacetone alcohol 123-42-2	X
Propylene glycol monomethyl ether 107-98-2	X
2-Butoxyethanol 111-76-2	X

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects

Canada

Component	NPRI - National Pollutant Release Inventory
-----------	---------------------------------------------

Dipropylene Glycol Monomethyl Ether 34590-94-8	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Diacetone alcohol 123-42-2	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
Propylene glycol monomethyl ether 107-98-2	Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999
2-Butoxyethanol 111-76-2	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999

16. OTHER INFORMATION

HMIS:	Health	Flammability	Reactivity	Personal Protection
	2 *	2	0	X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
 STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
 A2 - Suspected Human Carcinogen
 A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans
 Group 2A - Probably Carcinogenic to Humans
 Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen
 Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date May-31-2015

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of MSDS